

Auto-Dialers



COMBI LIFT

Auto-Dialer with integrated hands-free box suitable for installation behind car operating panel, ideal for surface-mounted COPs.

MAIN FEATURES

- Integrated intercom (Full-duplex, maximum speaker power 1W).
- Buffer battery management 12V and efficiency test.
- Technical alarms management: power supply presence, low and/or inefficient battery.
- PSTN line input.
- 1 outputs relay enabled by remote or alarm event.
- Protocols Management for call-center (ex. Ademco Contact ID, P100).
- Simplified wiring system for speaker modules (Speakerlift) 2 wires.
- GSM line input with GSM300 device (optional).
- Programming by telephone keypad; locally and remotely.
- Programming via graphic display DISP903.
- Programming via Vegacom APP (only if there is GSM300).
- Programming via Managerlift (Vega Cloud).
- Memory capacity up to 10 phone numbers.
- 32 customizable messages divided into 4 languages.
- Inductive loop facility for the hard-of-hearing.
- 4 types of inputs: alarm input, alarm filter input, technical alarm input and reset alarm input.
- Sent and acknowledged alarm signals.

BENEFITS



INTEGRATED HANDS-FREE KIT



BATTERY LEVEL CONTROL



SIMPLIFIED WIRING SYSTEM

SIZE
180x79x19 mm

TECHNICAL DATA
Input power supply: from 9V to 24V DC and AC.
Output power supply: 12V dc 500mA.
Inputs: 4x opto isolator 5-50V 50 mA.
Outputs: 1x Relay, 2x Open Collectors.