



Runder Schlüsselkontakt  
/ Round key selector



Quadratischer Schlüsselkontakt  
/ Squared key selector

## KL-KEY

Schlüsselschalter mit Quittierung.  
Illuminated key selector.



### HAUPTFUNKTIONEN

- Struktur: Schlüsselblock, im Polycarbonatkörper mit beleuchtbarem Ring.
- Ringe: ABS, galvanisiert (Gold und Chrom), verfügbar in der Ausführung ROUND und SQUARE.
- Vorderseite: Ring aus Stahl und Schlüsselblock.
- Montage: der Taster wird von vorne in einen Durchbruch  $\varnothing$  32,2 eingesetzt und von hinten mit einem Schraubring befestigt.
- Plattenstärke: von 0,7 bis 3 mm.
- Verfügbare Modelle:
  - K#2P1E (2 Positionen, 1 Abzug);
  - K#2P2E (2 Positionen, 2 Abzüge);
  - K#1P1E (mit Federrückholung).
- Anschluss: mit Drähten.
- Stromversorgung Leuchtring: (4XLED) 12 oder 24 VDC I=20mA.
- Schutz: IP51.
- Optional: Schlüsselkontakt auf VENUS XL.

### MAIN FEATURES

- Body: Key block integrated in polycarbonate body with illuminated halo.
- Bezel: metallized ABS (gold or chrome); it is available in the ROUND and SQUARE version.
- Front part: Stainless Steel ring and key block.
- Mounting: it is put into the 32,2 cutout from the front and fixed by threaded ring.
- Faceplate thickness: 0,7 to 3mm.
- Available items:
  - K#2P1E (2 position/1 extraction);
  - K#2P2E (2 positions/2 extractions);
  - K#1P1E (with spring return).
- Wiring: by wires.
- Halo voltage: (4XLED) 12 or 24 VDC I=20mA
- Degree of protection: IP51.
- Optional: key block for VENUS XL model