

Auto-Dialers



COMBI BASIC

Auto-Dialer with din bar to be installed in the control panel.

MAIN FEATURES

- Protocols Management for call-center (ex. Ademco Contact ID, P100).
- Simplified wiring system for speaker modules (Speakerlift) 2 wires.
- GSM line input with GSM300 device (optional).
- Programming by telephone keypad; locally and remotely.
- Programming via graphic display DISP903.
- Programming via Vegacom APP (only if there is GSM300).
- Programming via Managerlift (Vega Cloud).
- Memory capacity up to 10 phone numbers.
- 32 customizable messages divided into 4 languages.
- Inductive loop facility for the hard-of-hearing.
- 4 types of inputs: alarm input, alarm filter input, technical alarm input and reset alarm input.
- Sent and acknowledged alarm signals.

BENEFITS



SIMPLIFIED WIRING SYSTEM

SIZE
111x92x50 mm

TECHNICAL DATA

Input power supply: from 11V to 14V DC.
Output power supply: 12V DC 500 mA.

Inputs: 4x opto isolator 5-50V 50mA.
Outputs: 2 open collectors.

EXPANSION BOARDS

CB LINE

Analog line interface.

MAIN FEATURES

- PSTN analog line input.

CB RELE

Relay board.

MAIN FEATURES

- 2 Relay outputs for piloting locally and remotely or with alarm event.

CB BAT

UPS board.

MAIN FEATURES

- Allows for supply Auto-Dialer with voltage between 9 and 24 V AC/DC.
- Power supply filter against interferences.
- Buffer battery management 12V and efficiency test.
- Power supply battery and battery charger function.
- Technical alarms management: low and /or inefficient battery, no electricity.



BENEFITS



BATTERY LEVEL CONTROL