

Display TFT

TFT Display



IRIS 4.3"



Display alta risoluzione piano e cabina.
High resolution landing and car position indicator.

FUNZIONI PRINCIPALI

- Facile configurazione tramite PC.
- Aggiornamento tramite SD Card.
- Completamente personalizzabile (sfondo, frecce, piani, logo e segnali).
- UNI EN 81-70.
- Inserimento immagini e audio (per i display di cabina).
- Funzione stand-by.
- Tastierino a bordo per le principali funzioni (volume, interfaccia di comunicazione, primo piano, luminosità, durata stand-by).
- Luce emergenza integrata (per i display di cabina).
- Comunicazione: seriale Vega, CAN, RS485, parallela, per pilotaggio sensori magnetici.
- Case di protezione e fissaggio.
- Montaggio: sia verticale che orizzontale.
- Calendario (per display di cabina).

MAIN FEATURES

- Easy configuration via PC.
- Updating by SD Card.
- Customizable background, arrows, floors, logo and signalling.
- UNI EN 81-70.
- Customizable background with pictures and sounds (for car position indicators).
- Energy saving system mode (stand-by).
- Easy keypad for the selection of the main features (buzzer volume, communication interface, first floor, brightness, stand-by duration).
- Integrated emergency light (for car position indicators).
- Communication interface: Vega serial, RS485, CAN, parallel and magnetic sensors.
- Mounting: protection case.
- Mounting: horizontal and vertical.
- Calendar (for car position indicators).

OPZIONALE / OPTIONAL

- Sintesi vocale / Voice synthesizer.
IRIS 4.3" ANTIVANDALO / VANDAL PROOF:
- Spessore vetro 10mm / 10mm glass thickness.
 - Tenuta stagna / Watertight seal.



Iris 4.3" verticale e orizzontale /
Vertical and horizontal Iris 4.3".



SIRIO
Easy software di programmazione dedicato / Easy dedicated programming software.

Dimensioni / Dimensions: 147x79 mm.
Area visibile / Visible area: 95.3 x 53.8 mm.
Scasso / Cut out: 95.3 x 53.8 mm (R3.15).
Ingombro / Encumbrance: 160x80
Risoluzione / Resolution: 480(RGB) x 272 -WVGA.
Pixel (mm): 0.198x0.198mm.
Colori / Colours: 65.000.
Consumo d'energia / Energy consumption: 220mA.
Alimentazione / Power supply: 12/24 Vdc.
Temperatura / Temperature range: -20/+70°C.
Versione parallela (Ingressi un polo per piano) / parallel version (inputs 1 pole for floor): connettori precablati.
Cablaggio / Wiring: Connettori precablati / wiring connectors.